



2 Half Height Device Bay,  
Single Power Supply, 1-U Rackmount/Desktop Enclosure

With Support for:

- SCSI Narrow
- SCSI Ultra Wide
- SCSI Ultra II LVD
- SCSI Ultra III LVD

*VERSATILE &  
ULTRA SLIM PROFILE*



Note: Shown With  
Tape Drives Installed

- Ultra Slim Profile Design Available in Rackmount or Desktop Configuration
- Available in Narrow and Ultra Wide SCSI or Low Voltage Differential (LVD) Interfaces  
Mounts up to Two 5.25 Inch Half-Height Devices With Support for Hard Drives, CD Drives, Magneto Optical Drives, and Tape Drives
- 19 Inch Rackmount Enclosure Meets RETMA Standards - Includes Chassis Slides (Desktop Configuration Available)
- Quality All-Metal Construction and Agency Approved Components Ensure Compliance with UL, CSA, TUV and FCC Standards
- Flexibility in Configuration Options Including Choice of Drive Trays, a Variety of Cables and Connectors, and
- Custom Painting to Match any Product, System or Facility Decor
- Custom Backlit Logos Available
- Quality Product Made in the U.S.A. - Three Year Warranty





**ELECTRICAL**

**AC Input Power**

Voltage 115/230 VAC ± 15% (Auto Switching)  
Frequency 47 to 63Hz  
Protection 4A/250V Fuse

**DC Output Power**

Continuous 65W  
+5VDC 4A  
+12VDC 2A

**ENVIRONMENTAL**

**Temperature**

Operating 0 to 50° C  
Storage -25 to 85° C

**Humidity**

0 to 95%  
Non-Condensing

**Altitude**

Operating 0 to 10,000 Feet  
Storage 0 to 30,000 Feet

**PHYSICAL**

**Installation**

Fixed Mount Rackmount, or Desktop

**Dimensions**

17.00in. w x 12.75in. d x 1.75in. h

**Weight**

15Lbs

**CONFIGURATION**

**Device Bays**

Supports up to Two 5.25in. Half-Height Devices

**Power Supplies**

One 65W Power Supply

**CONNECTOR LOCATIONS**

**Standard**

Four VHDCI  
Two DB-9

**COOLING**

Two 12VDC, 6CFM Fans Provide Front to Rear Cooling

**ACCESS**

**Cabling**

Through Easy to Remove Top Cover

**ADDITIONAL OPTIONS**

Custom Backlit Logos  
Logo Silkscreening  
Beige, Black or White (Custom Colors Available)

